

Docker Basics

Published: 2019-04-03

Updated: 2019-04-03

Web: <https://fritzthecat-blog.blogspot.com/2019/04/docker-basics.html>

[Docker](#) is for deployment. It is a *virtualization at operating-system level*. When you pack your application into a docker image and run that image, the application will believe that it has the whole computer on its own. All dependencies will be in that image, as configured in a [Dockerfile](#) of your application together with build- and runtime-environment variables. You don't depend on any software being installed on your deployment target.

Virtualization is what [virtual machines](#) did for us until now, but docker can do that more lightweight and much faster. Originally it was available on LINUX only, because the LINUX kernel can somehow "duplicate" itself ([cgroups](#), [namespaces](#)), which feels like more than one operating-system "instances" running on the same hardware. For WINDOWS 10 this is available as "[Hyper V](#)" feature, you must activate virtualization in the BIOS of your computer; alternatively run a LINUX VM that hosts the docker installation for WINDOWS. Such said you will understand that, instead of a VM, docker has to be installed on the machine where you want to run your docker image.

You can find all what's in this Blog on the [docker homepage](#). Lots of docker images are [available freely](#) on the internet.

Mind that

- *docker aims at the [cloud](#), the packed app may be expected to be a [12-factor](#) app*
- *docker doesn't provide operating-system-independence, the target operating-system must support the packed app*
- *all data that a dockerized app writes to the file system it runs upon will be lost when its container gets removed*
- *two Java apps packed into two docker images will carry two [JREs](#) and not share them*
- *all dockerized Java apps will see the same number of CPU cores and the same memory amount, so if they scale themselves (like a JVM does), they may [overuse system resources](#) (switch to [Java 9](#) or newer and use JVM options `-XX:+UnlockExperimentalVMOptions -XX:+UseCGroupMemoryLimitFo`).*

Build Image, Run Containers

The **image** is what you **build**. The **container** is what you **run**.

The image won't change, it's the template for the container, while the container is a process that can take on states. You can instantiate many containers from one image. Containers are still present after they terminated, unless they were created using the `--rm` flag, like in `docker run --rm imagename`.

Useful Commands

You can manage your docker platform by [lots of commands](#) that all start with "docker".

| Purpose | Command |
|--|--|
| List all images installed on computer | <code>docker images</code> <code>docker image ls</code> |
| List all running containers on computer | <code>docker ps</code> <code>docker container ls</code> |
| List all running and stopped containers on computer | <code>docker ps -a</code> <code>docker container ls -a</code> |
| Instantiate a container from image "hello-world", with download if the image is not present | <code>docker run hello-world</code> |
| Look at the logs of container "mysql" | <code>docker logs --follow mysql</code> |
| Terminate the container with identity "mysql" | <code>docker stop mysql</code> |
| Start again the stopped container with identity "mysql", using the same file system | <code>docker start mysql</code> |
| Stop and start again the running container with identity "mysql" | <code>docker restart mysql</code> |
| Remove a container "hello-world" | <code>docker rm hello-world</code> |
| Remove an image "hello-world" | <code>docker rmi hello-world</code> |
| Start an interactive shell (bash) inside a running container "mysql" | <code>docker exec -it mysql bash</code> |
| Copy a file <code>/opt/mysql/my.ini</code> from a container "mysql" into current directory (".") | <code>sudo docker cp mysql:/opt/mysql/my.ini .</code> |
| Display the layers inside the image "hello-world" | <code>docker history hello-world</code> |
| Create an image out of the app in current directory where a <i>Dockerfile</i> exists | <code>docker build .</code> |
| Remove all stopped containers, unused images and other resources | <code>docker system prune -a</code> |
| Remove all images not connected to a container | <code>docker image prune -a</code> |

Dockerfile Keywords

A *Dockerfile* normally is placed in the root directory of the project that needs to be packed into a docker image. It's like a *C makefile*, or a Java/Maven *pom.xml*, but it has [its own syntax](#). Following is a short reference of some important keywords used in such a file.

| Keyword | Meaning |
|---------|---|
| # | Exclusively at line start, opens a comment or a parser-directive like "# directive=...", "# syntax=...", "# escape=..." |
| | The docker image this app builds on. A Java app would put a JRE here. Dependencies of |

| | |
|--------------------------------|---|
| <u>FROM</u> | dependencies need not to be listed. A valid <i>Dockerfile</i> always starts with FROM. |
| <u>ARG</u> | Buildtime variable, optionally with default-value. Can be set or overwritten by an option in the <code>docker build</code> command. An ENV- or ARG-variable <code>xxx</code> can be used inside a <i>Dockerfile</i> via <code>\$\$\$xxx</code> or <code>\${xxx}</code> . |
| <u>ENV</u> | Runtime variable for OS-environment of the contained app. Can be overwritten by an option in the <code>docker run</code> command. |
| <u>LABEL</u> | Metadata, can be recalled by <code>docker inspect</code> . |
| <u>EXPOSE</u> | The port where the contained app listens, defaults to a TCP type port. |
| <u>VOLUME</u> | Creates a directory (or mount point) shared with the outside world that will not be removed when the container gets removed. |
| <u>WORKDIR</u> | Sets the working directory for all RUN, CMD, ENTRYPOINT, COPY, ADD statements following in the <i>Dockerfile</i> . In case WORKDIR doesn't exist, it will be created. |
| <u>USER</u> | Sets the system-user for all RUN, CMD, ENTRYPOINT statements following in the Dockerfile. |
| <u>COPY</u> | Buildtime, copies files from file system into the image to build. |
| <u>ADD</u> | Buildtime, copies files from file system or URLs from the network into the image to build. |
| <u>RUN</u> | Buildtime, executes the command to the right of RUN. |
| <u>CMD</u> | Runtime, starts the contained app on <code>docker run</code> . Only one CMD statement is possible in a <i>Dockerfile</i> . |

Mind that setting the image's name inside a *Dockerfile* is [not supported!](#)

[Layers and Gotchas](#)

A *Dockerfile* like this one

```
FROM debian:jessie
ADD large_file /var/www/large_file
RUN chown www-data /var/www/large_file
RUN chmod 756 /var/www/large_file
```

that packs a `large_file` of 1 GB size and then changes its access rights will lead to a 3 GB image with following layers:

| IMAGE | CREATED | CREATED BY | SIZE |
|--------------|----------------|---|-------|
| 49b4a4ea228a | 36 seconds ago | /bin/sh -c chmod 756 /var/www/large_file | 1.074 |
| 09d77316932b | 2 minutes ago | /bin/sh -c chown www-data /var/www/large_file | 1.074 |
| 7adb7c72c3ef | 2 minutes ago | /bin/sh -c #(nop) ADD file:a86f6dedfb4ba54972 | 1.074 |
| f50f9524513f | 8 weeks ago | /bin/sh -c #(nop) CMD ["/bin/bash"] | 0 B |
| <missing> | 8 weeks ago | /bin/sh -c #(nop) ADD file:b5391cb13172fb513d | 125.1 |

That means, every build step like FROM, RUN, COPY, ADD creates a new [layer](#), and files referenced in the commands executed there will be copied always newly into the image.

This also affects final cleanups of left-over files, they would be deleted in the topmost layer only. Docker observes the file system and notices any change after a build step (resulting in a new layer), but it doesn't associate steps and draw conclusions.

Workaround:

Commands that change the file system should be linked together by the '&&' operator to just one command:

```
RUN apt-get update \  
    && apt-get install -y vim \  
    && rm -rf /var/lib/apt
```

A `chown` could be done by a preparing `"RUN usermod -u 1000 www-data"`.

Alternatively the container can be started by a script that provides all necessary circumstances:

```
docker run hello-world --entrypoint=/bin/myscript.sh
```

In the latter case the `/bin/myscript.sh` should be inside the docker image.